

Product	Contacts: 4, Female cable connector, screw, with laser marked screw terminal contacts
Area	M8 Series 768
Article number	99 3376 100 04

Illustration	Scale drawing	Contact Arrangement															
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1,70</td> <td>-0,50</td> </tr> <tr> <td>2</td> <td>1,08</td> <td>1,45</td> </tr> <tr> <td>3</td> <td>-1,70</td> <td>-0,50</td> </tr> <tr> <td>4</td> <td>-1,08</td> <td>1,45</td> </tr> </tbody> </table>		X	Y	1	1,70	-0,50	2	1,08	1,45	3	-1,70	-0,50	4	-1,08	1,45
	X	Y															
1	1,70	-0,50															
2	1,08	1,45															
3	-1,70	-0,50															
4	-1,08	1,45															

You can find the item description on the next page.

Technical data

Common values

Connector Design	Cable socket
Connector locking system	bolted
Termination	screw
Wire gauge (mm)	0,14-0,50 mm ²
Wire gauge (AWG)	26-20
Cable outlet	3,5 - 5 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Cable data

Approval 1	UL listed
------------	-----------

Electrical values

Rated voltage	30
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	III
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP67

Material

Material of contact	CuZn (Messing)
Contact plating	Au (gold)
Material of contact body	PA (UL 94 HB)

Product **Contacts: 4, Female cable connector, screw, with laser marked screw terminal contacts**

Area **M8 Series 768**
Article number **99 3376 100 04**

Item description

